

AMERICA ASIA GROUP CO.

2485 Roanoke Rd, San Marino, California, 91108, USA

Tel:626-309-0198 Fax:626-309-0185 Email:aagc888@aol.com web:aagcusa.com

Indoor Standoff Insulators

These standoff insulators are constructed of the highest quality wet process electrical porcelain. Glaze is ANSI Gray (Munsell 5GB 7.0/0.4). Inserts are of brass tapped 11/16" deep (full thread). All are tested electrically after assembly.



AAGC PartNo.	PPC No.	Dimensions inches		style No.	Insert Thread	Min. Creep Inches	Strike Inches	Rating kV	Strength Rating in lb.				Std. Pkg.
		Dia	Height						EA. End	Bil KV.	Cantilever 5/8 above too	Tension	
2010	70100	2	2 1/2	1	3/8 #16	3	25	2.5	45	550	1375	6500	25
2012	70105	2	3 1/2	1	3/8 #16	4 1/2	3 1/2	5	75	350	1400	6500	25
2013	70110	2	5 1/8	1	3/8 #16	7	5 1/8	8.7	95	225	1600	6500	25
2020	70115	2 1/2	2 9/16	1	3/8 #16	3 1/2	2 9/16	2.5	60	525	1900	8000	25
2021	70125	2 1/2	3	1	3/8 #16	4 1/2	3	5	60	425	1775	8000	25
2022	70130	2 1/2	4	1	3/8 #16	7	4	8.7	75	425	1775	8000	25
2023	70135	2 1/2	5	1	3/8 #16	7 1/2	5	8.7	95	300	1700	8000	25
2024	70140	2 1/2	6	1	3/8 #16	10 1/2	6	15	110	225	1850	8000	25
	70145	2 3/4	3 1/8	1	3/8 #16	5	3 1/8	5	60	500	1900	8500	25
2030	70150	3 1/8	2 5/8	1	1/2 #13	4	2 5/8	5	60	525	1800	10000	25
2031	70151	3 1/8	2 5/8	1	3/8 #16	4	2 5/8	5	60	525	1800	10000	25
2032	70152	3 1/8	2 5/8	1	1/2 #13 3/8 #16	4	2 5/8	5	60	252	1800	10000	25
2033	70155	3 1/8	3 3/8	1	3/8 #16	5	3 3/8	5	60	515	1925	10000	25
2034	70160	3 1/8	3 3/8	1	1/2 #13	5	3 3/8	5	60	515	1925	10000	25
2035	70165	3 1/8	4	1	1/2 #13	6	4	7.5	75	510	2000	10000	25
2036	70169	3 1/8	5	1	3/8 #16	7 1/4	5	8.7	95	275	1725	10000	25
2037	70170	3 1/8	5	1	1/2 #13	7 1/4	5	8.7	95	275	1725	10000	25
2038	70174	3 1/8	6	1	3/8 #16	10 5/8	6	15	110	260	1600	8000	25
2039	70175	3 1/8	6	1	3/8 #16 1/2 #13	10 5/8	6	15	110	260	1600	87000	25
2040	70176	3 1/8	6	1	1/2 #13	10 5/8	6	15	110	260	1600	8000	25
2050	70185	3 1/2	3	1	1/2 #13	5	3	5	60				25
2051	70190	3 1/2	3 1/2	1	1/2 #13	6 1/4	3 1/2	7.5	75	700	2400	12000	25
2052	70195	3 1/2	4 1/2	1	1/2 #13	6 1/2	4 1/2	8.7	95	400	1725	12000	25
	70200	3 1/2	3 1/4	2	1/2 #13	4	3 1/4	5	60	800	2750	15000	25
	70205	4	3 15/16	2	1/2 #13	7 5/8	3 15/16	8.7	75	750	2350	20000	18
2060	70210	4	4 5/8	2	1/2 #13	9 1/4	4 5/8	8.7	95	575	1900	20000	25
2061	70214	4	6	2	3/8 #16	12 3/8	6	15	110	375	2000	20000	120
2062	70215	4	6	2	1/2 #13	12 3/8	6	15	110	375	2000	20000	120